

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

ALU660 CLP

Revision 0

Revision date 2014-07-18

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Aluminium HT Lube ALU660 - CLP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description Aerosol.

1.3. Details of the supplier of the safety data sheet

Company Tough Technology Products Ltd Ltd
Address 114 Washway Road
Sale Pocklington
Cheshire
M33 7RF
United Kingdom
Web www.ttproducts.com
Telephone +44 800 772 0996
Email sales@ttproducts.com
Email address of the competent person sales@ttproducts.com

1.4. Emergency telephone number

Emergency telephone number +44 800 772 0996
9.00am - 5.00pm Mon-Fri

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 67/548/EEC F+; R12 Xi; R38 R52/53-67
Symbols: F+: Extremely flammable. Xi: Irritant.
Main hazards Extremely flammable. Irritating to skin. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.
2.1.2. Classification - EC 1272/2008 Aerosols 1: H222; Aerosol 1, 2, 3: H229; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 3: H412;

2.2. Label elements

Hazard pictograms Contains: Naphtha (Petroleum) Hydrotreated, Light.



Signal Word Danger

Hazard Statement Aerosols 1: H222 - Extremely flammable aerosol.
Aerosols, 1, 2, 3: H229 - Pressurised container: May burst if heated.
Skin Irrit. 2: H315 - Causes skin irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.

ALU660 CLP

Revision 0

Revision date 2014-07-18

2.2. Label elements

Precautionary Statement: Prevention	Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
	P102 - Keep out of reach of children.
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211 - Do not spray on an open flame or other ignition source.
	P251 - Do not pierce or burn, even after use.
Precautionary Statement: Storage	P271 - Use only outdoors or in a well-ventilated area.
	P273 - Avoid release to the environment.
	P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

2.3. Other hazards

Other hazards	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 - IF ON SKIN: Wash with plenty of water/. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up. P501 - Dispose of contents/container to / in accordance with national regulations.
----------------------	---

SECTION 3: Composition/information on ingredients

3.1. Substances

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Butane	601-004-00-0	106-97-8	203-448-7	01-2119474691-32	20 - 30%	F+; R12
Propane	601-003-00-5	74-98-6	200-827-9	01-2119486944-21	20 - 30%	F+; R12
SBP 60/95 Low n-Hexane		64742-49-0	265-151-9	01-2119486291-36 01-2119486291-36	20 - 30%	F; R11 Xn; R65 Xi; R38 N; R51/53 R67
Xylene (Xylene, o-,m-,p-or mixed isomers)	601-022-00-9	1330-20-7	215-535-7	01-2119488216-32	1 - 10%	R10 Xn; R20/21 Xi; R38

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Butane	601-004-00-0	106-97-8	203-448-7	01-2119474691-32	20 - 30%	Flam. Gas 1: H220;
Propane	601-003-00-5	74-98-6	200-827-9	01-2119486944-21	20 - 30%	Flam. Gas 1: H220;
SBP 60/95 Low n-Hexane		64742-49-0	265-151-9	01-2119486291-36 01-2119486291-36	20 - 30%	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411;
Xylene (Xylene, o-,m-,p-or mixed isomers)	601-022-00-9	1330-20-7	215-535-7	01-2119488216-32	1 - 10%	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to respiratory system.
Eye contact	May cause irritation to eyes.

ALU660 CLP

Revision 0

Revision date 2014-07-18

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	May cause irritation to skin.
Ingestion	May cause irritation to mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention if irritation or symptoms persist.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

	Use extinguishing media appropriate to the surrounding fire conditions.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

	Ensure adequate ventilation of the working area.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

6.4. Reference to other sections

	See section 8 and 13 for further information.
--	---

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--

7.3. Specific end use(s)

	No data is available on this product.
--	---------------------------------------

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

	Occupational exposure controls.
--	---------------------------------

8.1.1. Exposure Limit Values

Butane	WEL 8-hr limit ppm: 600	WEL 8-hr limit mg/m3: 1450
	WEL 15 min limit ppm: 750	WEL 15 min limit mg/m3: 1810
Xylene (Xylene, o-,m-,p-or mixed isomers)	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 220
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 441

ALU660 CLP

Revision 0

Revision date 2014-07-18

8.2. Exposure controls



8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear protective clothing.

Eye / face protection

In case of splashing, wear:.. Approved safety goggles.

Skin protection - Handprotection

Chemical resistant gloves (PVC).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State	Aerosol
Colour	Grey
Odour	Aromatic

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Burning produces obnoxious and irritating fumes.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

12.2. Persistence and degradability

No data is available on this product.

12.3. Bioaccumulative potential

No data is available on this product.

12.4. Mobility in soil

No data is available on this product.

12.5. Results of PBT and vPvB assessment

No data available.

ALU660 CLP

Revision 0

Revision date 2014-07-18

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

Disposal methods

Contact a licensed waste disposal company.

Disposal of packaging

Do NOT reuse empty containers. Empty containers can be sent for disposal or recycling.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

ADR/RID

2

Subsidiary risk

see SP63

IMDG

2

Subsidiary risk

see SP63

IATA

2

Subsidiary risk

see SP63

14.4. Packing group

Packing group

-

14.5. Environmental hazards

Environmental hazards

No

Marine pollutant

No

ADR/RID

Hazard ID

-

Tunnel Category

(D)

IMDG

EmS Code

F-D S-U

IATA

Packing Instruction (Cargo)

203

Maximum quantity

150 kg

Packing Instruction
(Passenger)

203

Maximum quantity

75 kg

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

ALU660 CLP

Revision 0

Revision date 2014-07-18

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	<p>COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p> <p>REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p>
--------------------	--

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out for this product.

SECTION 16: Other information**Other information**

Text of risk phrases in Section 3	<p>R10 - Flammable R11 - Highly flammable. R12 - Extremely flammable. R20/21 - Harmful by inhalation and in contact with skin. R38 - Irritating to skin. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 - Harmful: may cause lung damage if swallowed. R67 - Vapours may cause drowsiness and dizziness.</p>
Text of Hazard Statements in Section 3	<p>Flam. Gas 1: H220 - Extremely flammable gas. Flam. Liq. 3: H226 - Flammable liquid and vapour. Acute Tox. 4: H312 - Harmful in contact with skin. Skin Irrit. 2: H315 - Causes skin irritation. Acute Tox. 4: H332 - Harmful if inhaled.</p>

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.