



# SUPER-6

SUPER-6 penetrating oil  
A premium lubricant and moisture repellent  
Part No SUPER6400

## Product Description

Super 6 is a high performance universal aerosol which performs the functions of 6 different products. It has been designed to appeal to the largest possible number of markets including Industrial, automotive, marine and domestic

## Typical Applications

Can be used as a premium lubricant, moisture repellent, for surface protection, for rust penetration, as a surface cleaner and a rubber rejuvenator.

## Application Features

A light film lubricant BUT with a heavy duty performance in penetrating and lubrication. Super-6 lubrication spray dries fast and leaves a clear, non-staining film that doesn't stick or make a mess, so it won't attract dirt. Effective in a temperature range from -100°F to 500°F

## General Information

For safe handling of this product consult the Material Safety Data Sheet.

## Direction Of Use

Prior to use shake can well  
Spray onto area to be lubricated from a distance of 10-20cms  
Allow to soak in





**Tough Technology Products**  
Eaton Place Business Centre, 114 Washway Road, Sale  
Cheshire, M33 7RF, England  
Tel: Tel: 0800 772 0996



# SUPER-6

SUPER6 penetrating oil  
A premium lubricant and moisture repellent  
Part No SUPER6400

## Physical & Chemical Properties

<b>Colour:</b>	Brown
<b>Odour:</b>	characteristic
<b>State:</b>	Aerosol

## Presentation

Aerosol: ... . . . . 400ml

## Storage

Always store aerosols away from sources of heat, including direct sunlight and in dry conditions. Avoid extremes of temperature and moisture. A stable, cool, dry ambient environment is most suitable.

## Data Ranges

The data contained in this data sheet may be reported as typical value and/or range. Values are based on actual test data and are verified on a regular basis.

## Disclaimer

**IMPORTANT:** The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Tough Technology Products Limited expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; **NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANT ABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN.** The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.

Before handling this material, read and understand the MSDS (Material Safety Data Sheet) for additional information on personal protective equipment and for safety, health and environmental information.

