



Tough Technology Products

Eaton Place Business Centre, 114 Washway Road, Sale
Cheshire, M33 7RF, England
Tel: 0800 772 0996

Leading Edge Technology



X1200

X1200 High Temperature Anti-Seize Assembly Spray

Part No X1200A

Product Description

X1200 High Temperature Anti-Seize Assembly Spray

Typical Applications

X1200 High Temperature Anti-Seize Assembly Spray is a premium specification assembly paste. Manufactured without compromise this product has been designed to perform in the most arduous of applications. Assembled units can be easily taken apart with the appropriate tooling, even after years.

Application Features

- Protects against galvanic action and corrosion
- Outstanding temperature range (-180 deg C to 1200 deg C)
- Withstands high pressure
- Resists Water, Salt, chemical vapours, solvents etc
- Makes assembly and dismantling easy
- Very economical
- Contains no Nickel

General Information

For safe handling of this product consult the Material Safety Data Sheet.

Direction Of Use

- Clean and degrease the surfaces
- Apply the **X1200** evenly
- Assemble the parts



Tough Technology Products
Eaton Place Business Centre, 114 Washway Road, Sale
Cheshire, M33 7RF, England
Tel: 0800 772 0996



X1200

X1200 High Temperature Anti-Seize Assembly Spray

Part No X1200A

Physical & Chemical Properties

FORM: Aerosol
COLOUR: Grey
ODOUR: Aromatic

Presentation

Aerosol: 400ml

Storage

Store between 5 and 25°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

Data Ranges

The data contained in this data sheet may be reported as typical value and/or range. Values are based on actual test data and are verified on a regular basis.

Disclaimer

IMPORTANT: The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, †Tough Technology Products Limited† expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; **NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN.** The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.

Before handling this material, read and understand the MSDS (Material Safety Data Sheet) for additional information on personal protective equipment and for safety, health and environmental information.

